



DCT-ST5012D1

SUBWOOFER DANYCATECH 12" 5000RMS



SPECIFICATIONS

Power	10000 WATTS
RMS Power	5000 RMS
Impedance	1+1 Ohm
Resonance Frequency	35,3 (Hz)
Frequency Response	20-120 Hz
Voice Coil Diameter	4 inch
Sensitivity	85,5 dB
Magnet	505 Oz

MOUNTING INFORMATION

Diameter A	mm	325
Diameter B	mm	303
Diameter C	mm	286
Diameter D	mm	260
Depth E	mm	115
Depth F	mm	17
Depth G	mm	243
Depth H	mm	281
Vd	L	9,772
Nt Wt.	Kg	31,5



THIELE SMALL PARAMETERS (PARALLEL)

FS Hz	35,3
Vas (L)	19,2
Dcr (Ohm)	0,4
Qms	5,163
Qes	0,611
Qts	0,546
BL (T/m)	51,071
Mms (g)	359,4
Xmax (mm)	20
Xmech (mm)	55
SD (msqM)	51,071

THIELE SMALL PARAMETERS (SERIES)

FS Hz	35,8
Vas (L)	19,9
Dcr (Ohm)	1,6
Qms	4,487
Qes	0,571
Qts	0,506
BL (T/m)	15,231
Mms (g)	367,5
Xmax (mm)	20
Xmech (mm)	55
SD (msqM)	51,071